

SPECIFICATIONS

MODEL NUMBER	POWER	BORE	STROKE	RAM SPEED		CAPACITY (TONS)	WEIGHT (LBS.)	SHIPPING DIMENSIONS		
				PRESS	RETURN			L	W	H
HFP-30	5 HP 230 1 phase	5"	12"	29 IPM	38 IPM	30	1,400	48"	62"	88"

Standard voltages available - please specify when ordering.


H FRAME PRESS 30 Ton

STANDARD FEATURES

- ✓ **Electric / Hydraulic operation** provides smooth, consistent pressing action.
- ✓ **Open sides** to facilitate work on long pieces.
- ✓ **Flat ram nose** can be easily changed to allow the user to adapt the press to a specific job.
- ✓ **Quality Baldor motor**, low speed.
- ✓ **Low speed pump** - quiet, dependable operation.
- ✓ **Self-locking table** design eliminates lateral movement.
- ✓ **Double-acting cylinder** permits pulling as well as pressing ram action.
- ✓ **Hydraulic power-lift** for vertical displacement of table.
- ✓ **Cylinder activation** is fingertip controlled, the more the hand lever is engaged the more the ram movement is accelerated. This allows the operator to control the proper speed for the task.
- ✓ **High capacity** 10 GAL. hydraulic oil reservoir.
- ✓ **Low pressure** hydraulic system maintains lower oil temperatures, resulting in higher efficiency and safer operation.

DIMENSIONS (INCHES)

MODEL	A	B	C	D	E	F
HFP-30	75	42	54	34	9	30



AVAILABLE OPTIONS

- VB-30** V BLOCKS matched pair.
- PR-30** Pressure regulator to limit the ram pressure.
- FSG-30** Front safety guard for operator protection.
- FPS-30** Foot pedal-electric solenoid valve for hands-free operation, c/w electric control panel.
- ASC-30** Adjustable stroke control c/w foot pedal-electric solenoid valve and electric control panel.
- 5-18** 18 Inch stroke cylinder.
- 5-24** 24 Inch stroke cylinder.

Custom designs available
We Build Them your Way!