PRESS MASTER



| MODEL CFP-50 | KEY | SPECS. |
|------------------------------------|-------------|------------------|
| Tons of force (maximum) | | 50 |
| Approach speed (inches per minute) | | 140 |
| Press speed (inches per minute) | | 17 |
| Return speed (inches per minute) | | 210 |
| Table (left to right) | Α | 34 |
| Table (front to back) | В | 20 |
| U-Slot width | C | 4 |
| Daylight | D | 20.5 |
| Maximum stroke (adjustable) | Е | 15 |
| Throat | F | 13 |
| Floor to table | G | 34.5 |
| Front to back | Н | 58 |
| Height (overall) | I | 102 |
| Width | J | 38 |
| Clearance | K | 6 |
| Upper platen (left to right) | L | 34 |
| Upper platen (front to back) | M | 20 |
| Motor HP @ 1750 RPM | | 10 HP |
| Voltages available | 230 / 460 / | 575 3 PH. 60 HZ. |

C FRAME PRESS 50 TON

STANDARD FEATURES

- √ Pressure gauge.
- $\sqrt{}$ Pressure regulator.
- $\sqrt{}$ Adjustable speed control.
- Adjustable stroke control.
- $\sqrt{}$ Pressure reversal switch.
- √ Ram travel is guided by 4 , precision-ground rods.
- $\sqrt{}$ Jog mode used for simplifying setups.
- √ Dual Control your choice of using:

 (1) Moveable pedestal c/w dual electric palm buttons & extra emergency stop or
 - (2) Foot pedal.
- √ P.L.C. programmable control system.
- $\sqrt{}$ Quality BALDOR motor, low speed.
- $\sqrt{}$ Air-Cooled industrial oil cooler.
- √ All hydraulic and mechanical parts are standard in the industry, and available throughout North America.

| MODEL | WEIGHT (LBS.) | SHIPPING L X | | X H |
|--------|---------------|-----------------|-----|------|
| CFP-50 | 8,800 | 64" | 59" | 110" |

